

Class 1

Wavebar

Product Disclosure Information - Building product information requirements (BPIR)

Version: 2023-NOV

Product name	Wavebar®
Product line	Acoustic treatment, wall/ceiling materials
Product identifiers	Wavebar®

Product description

Wavebar® is a high-performance, flexible mass-loaded vinyl noise barrier, offering superior acoustic transmission loss.

It's composed of a mass loaded vinyl and a fabric backing layer. Provided in rolls, it can be cut to the required lengths prior to use.

It can be installed with mechanical fixing; tape or adhesive may be used to aid installation.

Relevant building code clauses

B1 Structure — B1.3.1, B1.3.2, B1.3.3 (j), B1.3.4

B2 Durability – B2.3.1 (b)

C3 Fire affecting areas beyond the fire source— C3.4 (a)

F2 Hazardous building materials — F2.3.1

Contributions to compliance

B2.3.1(b) (i) and (ii) and B2.3.2: Wavebar has a durability of at least 15 years when installed as per the installation guide (IG). Refer to the IG for further information.

C3: Fire affecting areas beyond fire sources - C3.4: Wavebar has a Group Number of 3 determined by ISO 5600 Part 1 and Part 2. Refer to the test report provided by BRANZ testing laboratory available upon request.

F2.3.1: Wavebar is safe when handled. There are no requirements for this product in order to comply with Acceptable Solution F2/AS1, First Edition Amendment 3, 2017.

G6: Wavebar is a non-rigid acoustic insulation that may be required to be applied to cavities, constructions or partitions in order that the building element achieves the required performance, referenced in Acceptable Solutions G6/AS1, First Edition Amendment 2, 1995.

Scope of use

Wavebar is manufactured for use on:

- Acoustic treatment as wall/ceiling materials, including within air handling plenums.
- External surfaces of ducts for HVAC systems.

Conditions of use

Wavebar must be installed as per the Installation Guide (IG).

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
Website		https://www.pyroteknc.com/products/wavebar/wavebar/
Technical Datasheet		https://www.pyroteknc.com/dmsdocument/18/WAVEBAR-TDS-311IP.pdf
Installation Guide (Installation)		https://www.pyroteknc.com/dmsdocument/150/Wavebar-Install-304-1IG.pdf

Contact details

Manufacturer location	Australia	China
Legal and trading name of manufacturer	Pyrotek Pty Ltd.	Pyrotek (ChuZhou) New materials Co., Ltd
Manufacturer address for service	147 - 149 Magowar Road Girraween NSW 2145 Australia	2880 QingLiu Road Suchu Modern Industrial Park Chuzhou City, Anhui Province 239000 China
Manufacturer website	www.pyroteknc.com/	
Legal and trading name of importer	Pyrotek Products Limited	
Importer NZBN	9429039874146	
Importer address for service	69 Cryers Road, East Tamaki, Auckland 2013, New Zealand	
Importer website	www.pyroteknc.com/	
Importer email	nzsales@pyrotek.com	
Importer phone number	+64 0 9 272 2056	

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

Appendix

Product Category: Internal linings, acoustic treatment and duct insulation

	Yes	No
Use to provide structural bracing		x
Use in wet areas	x	
Use in food preparation areas		x
Part of an intertenancy / abutting occupancy wall system	x	
Use in areas with surface fire obligations	x	
Part of a fire protected boundary or fire wall		x
Use in areas with near to sources of heat		x

Building code performance clauses

All relevant building code performance clauses listed in this document:

B1 Structure

B1.3.1

Buildings, building elements and *sitework* shall have a low probability of rupturing, becoming unstable, losing equilibrium, or collapsing during *construction* or *alteration* and throughout their lives.

B1.3.2

Buildings, building elements and *sitework* shall have a low probability of causing loss of amenity through undue deformation, vibratory response, degradation, or other physical characteristics throughout their lives, or during *construction* or *alteration* when the *building* is in use.

B1.3.3

Account shall be taken of all physical conditions likely to affect the stability of *buildings, building elements* and *sitework*, including:

(j) impact

B1.3.4

Due allowances shall be made for:

- a. the consequences of failure,
- b. the intended use of the *building*,
- c. effects of uncertainties resulting from *construction* activities, or the sequence in which *construction* activities occur,
- d. variation in the properties of materials and the characteristics of the site, and
- e. accuracy limitations inherent in the methods used to predict the stability of *buildings*

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

a. the life of the building, being not less than 50 years, if:

- (i) those *building elements* (including floors, walls, and fixings) provide structural stability to the *building*, or
- (ii) those *building elements* are difficult to access or replace, or
- (iii) failure of those *building elements* to comply with the *building code* would go undetected during both normal use and maintenance of the *building*.

b. 15 years if:

- (i) those *building elements* (including the *building* envelope, exposed plumbing in the subfloor space, and in-built chimneys and flues) are moderately difficult to access or replace, or
- (ii) failure of those *building elements* to comply with the *building code* would go undetected during normal use of the *building*, but would be easily detected during normal maintenance.

c. 5 years if:

- (i) the *building elements* (including services, linings, renewable protective coatings, and *fixtures*) are easy to access and replace, and
- (ii) failure of those *building elements* to comply with the *building code* would be easily detected during normal use of the *building*

C3 Fire affecting areas beyond the fire source

C3.4 Surface Linings

(a) materials used as internal surface linings in the following areas of *buildings* must meet the performance criteria specified below:

Area of <i>building</i>	Performance determined under conditions described in ISO 9705: 1993	
	<i>Buildings not protected with an automatic fire sprinkler system</i>	<i>Buildings protected with an automatic fire[glossary] sprinkler system</i>
Wall/ceiling materials in sleeping areas where care or detention is provided	Material Group Number 1-S	Material Group Number 1 or 2
Wall/ceiling materials in exitways		
Wall/ceiling materials in all occupied spaces in importance level 4 <i>buildings</i>		
Internal surfaces of ducts for <i>HVAC systems</i>		
Ceiling materials in crowd and sleeping uses except <i>household units</i> and where care or detention is provided	Material Group Number 1-S or 2-S	Material Group Number 1 or 2
Wall materials in crowd and sleeping uses except <i>household units</i> and where care or detention is provided.	Material Group Number 1-S or 2-S	Material Group Number 1, 2, or 3
Wall/ceiling materials in occupied spaces in all other locations in <i>buildings</i> , including <i>household units</i>	Material Group Number 1, 2, or 3	Material Group Number 1, 2, or 3
External surfaces of ducts for <i>HVAC systems</i>		
Acoustic treatment and pipe insulation within air handling plenums in sleeping uses		

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction of buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.